



CC3X 1408

Simplicity, Rapidness & Safety

The CC3X is a purely resistive charging case enabling a **comprehensive control of the metrological line** during the meter installation on **all types of equipment** (single-phase, two-phase, three-phase).

Compatible with all connection controllers, it deploys all its abilities, associated to the **VB Pocket**.

Integrated in a suitcase on wheels for an easier transport, it combines SCLE SFE expertise in energy and measurement.



ADVANTAGES

- Control of running time
- 3 functioning modes: single-phase, two-phase, and three-phase
- Can be used immediately (no heating or cooling time)
- Compact and sturdy suitcase on wheels



CONTACT

SCLE SFE Marseille Agency

Parc des Aygalades Bât. 10
35 bd du Capitaine Gèze
13014 MARSEILLE - France

Phone No: +33 (0)4 91 03 04 24
erji@scle.fr - www.scle-sfe.fr

CC3X 1408

Simplicity, Rapidness & Safety

FUNCTIONALITIES

- Continuous flow rate with 15 minute safety time delay
- Selector switch: Single-phase 6KW, two-phase 2kW per phase to test the imbalance, three-phase 2kW per phase
- Automatic control of the correct connection of the neutral

TECHNICAL FEATURES

Simulated charge	Until 6kW single-phase
Self-powered	230V between phase 1 and neutral
Connection	By secured 4mm sockets / 32A
Protection	Magneto-thermal circuit breaker
Protection	Class 2
Thermal protection	Integrated in the box
Cooling	Permanent forced ventilation
Transport	Secure, reinforced and wheeled suitcase
Dimensions	56 x 35 x 23cm
Weight	< 10kg
Indicators	Indicator: fault, flowing, operational

ACCESSORIES

- | | | |
|---|--------------|---|
| 1 | Cordo | Set of 4x 4mm cords / 32A, 2m length (included) |
| 2 | Clips | Set of 4 dolphin clips (included) |
| 3 | Kit BEROMET® | Set of 4 BEROMET® clips + 4x 4mm socket adapters / BEROMET® |



CC3X 1408 1408 is designed and manufactured on our production site in Marseille, in collaboration with French associates and subcontractors.